

## subtle - Feature #137

### Add a method to find a client using it's pid number

03/14/2010 01:19 AM - Nicolas Reynolds

<b>Status:</b> Added	<b>Start date:</b> 03/14/2010
<b>Priority:</b> Urgent	<b>Due date:</b>
<b>Assignee:</b> Christoph Kappel	<b>% Done:</b> 0%
<b>Category:</b> Feature	<b>Estimated time:</b> 0.00 hour
<b>Target version:</b>	
<b>Description</b>	
Subtlex::Subtle.spawn() [0] will return the pid number of the command spawned, but it's no use since we can't find a client using it's pid as an argument for Subtlex::Client.find() [1].	
Use case: launcher scripts with advanced capabilities.	
[0] <a href="http://rdoc.subtle.de/subtle/classes/Subtlex/Subtle.html#M000036">http://rdoc.subtle.de/subtle/classes/Subtlex/Subtle.html#M000036</a>	
[1] <a href="http://rdoc.subtle.de/subtle/classes/Subtlex/Client.html#M000044">http://rdoc.subtle.de/subtle/classes/Subtlex/Client.html#M000044</a>	

### History

**#1 - 03/14/2010 09:35 PM - Christoph Kappel**

- Assignee set to Non member users

**#2 - 03/17/2010 08:24 PM - Christoph Kappel**

- Status changed from Unconfirmed to Confirmed

**#3 - 03/17/2010 08:25 PM - Christoph Kappel**

- Status changed from Confirmed to Feedback

**#4 - 03/17/2010 08:25 PM - Christoph Kappel**

- Status changed from Feedback to Added