

subtle - Bug #252

Fix segfault of subtle -k without running X

09/01/2011 01:30 PM - Christoph Kappel

Status:	Fixed	Start date:	09/01/2011
Priority:	High	Due date:	
Assignee:	Christoph Kappel	% Done:	100%
Category:	Bugfix	Estimated time:	0.00 hour
Target version:	Xi		
Description			
subtle -k raises an exception and segfaults, when run without a X and icons are used.			
<pre>subtle -k Using config `/home/unexist/.config/subtle/subtle.rb' <WARNING> Failed loading config `/home/unexist/.config/subtle/subtle.rb' <WARNING> StandardError: Failed opening display `(null)'     from /home/unexist/.config/subtle/subtle.rb:486:in `initialize' from /home/unexist/.config/subtle/subtle.rb:486:in `new'     from /home/unexist/.config/subtle/subtle.rb:486:in `<main>' Last 10 stack frames: subtle() [0x42300d] /lib/libc.so.6(+0x347a0) [0x7fc0b18537a0] /usr/lib/libX11.so.6(XFreePixmap+0xc) [0x7fc0b21c34cc] /usr/lib/ruby/site_ruby/1.9.1/subtle/subtlext.so(+0x10c67) [0x7fc0aef9fc67] /usr/lib/libruby.so.1.9(+0x6f628) [0x7fc0b2548628] /usr/lib/libruby.so.1.9(+0x709e5) [0x7fc0b25499e5] subtle() [0x4208ae] subtle() [0x423a15] /lib/libc.so.6(__libc_start_main+0xed) [0x7fc0b184013d] subtle() [0x405a59] Please report this bug at http://subforge.org/projects/subtle/issues zsh: abort DISPLAY= subtle -k</pre>			

History

#1 - 09/01/2011 03:44 PM - Christoph Kappel

- Status changed from Confirmed to Fixed
- % Done changed from 0 to 100

Applied in changeset [cec7b8c61f75](#).