

subtle - Bug #285

subtle fails to compile on OpenBSD

03/21/2012 06:00 AM - Timmy Steve

Status:	Fixed	Start date:	03/21/2012
Priority:	Urgent	Due date:	
Assignee:	Christoph Kappel	% Done:	100%
Category:	Bugfix	Estimated time:	0.00 hour
Target version:	Xi		
Description			
<pre>@\$ rake debug=yes checking for stdio.h... yes checking for stdlib.h... yes checking for stdarg.h... yes checking for string.h... yes checking for unistd.h... yes checking for signal.h... yes checking for errno.h... yes checking for assert.h... yes checking for sys/time.h... yes checking for sys/types.h... yes checking for sys/inotify.h... no checking for wordexp.h... no checking for execinfo.h... yes checking for X11/Xlib.h... yes checking for X11/Xpm.h... yes checking for X11/Xft/Xft.h... yes checking for X11/extensions/Xinerama.h... yes checking for X11/extensions/Xrandr.h... yes checking for X11/extensions/XTest.h... yes checking for select()... yes checking for rb_enc_set_default_internal()... yes Creating config.yml creating config.h subtle 0.10.3193 ----- Binaries.....: //usr/bin Configuration.....: /etc/xdg/subtle Extension.....: //usr/local/lib/ruby/site_ruby/1.9.1/subtle Xpm support.....: yes Xft support.....: yes Xinerama support.....: yes XRandR support.....: yes XTest support.....: yes Debugging messages...: yes CC build/subtle/shared.o CC build/subtle/array.o CC build/subtle/client.o CC build/subtle/display.o CC build/subtle/event.o CC build/subtle/ewmh.o CC build/subtle/grab.o CC build/subtle/gravity.o CC build/subtle/hook.o CC build/subtle/panel.o CC build/subtle/ruby.o cc1: warnings being treated as errors src/subtle/ruby.c: In function 'subRubyLoadSublets': src/subtle/ruby.c:3847: warning: passing argument 3 of 'scandir' from incompatible pointer type</pre>			

rake aborted!
Compiler failed with status 1

Tasks: TOP => default => build => subtle => build/subtle/ruby.o
(See full trace by running task with --trace)

#w/ --trace
\$ rake debug=yes --trace

- Invoke default (first_time)
- Invoke config (first_time)
- Execute config
- Invoke build (first_time)
- Invoke config
- Invoke subtle (first_time)
- Invoke config
- Invoke build/subtle/shared.o (first_time, not_needed)
- Invoke src/shared/shared.c (first_time, not_needed)
- Invoke build/subtle/array.o (first_time, not_needed)
- Invoke src/subtle/array.c (first_time, not_needed)
- Invoke build/subtle/client.o (first_time, not_needed)
- Invoke src/subtle/client.c (first_time, not_needed)
- Invoke build/subtle/display.o (first_time, not_needed)
- Invoke src/subtle/display.c (first_time, not_needed)
- Invoke build/subtle/event.o (first_time, not_needed)
- Invoke src/subtle/event.c (first_time, not_needed)
- Invoke build/subtle/ewmh.o (first_time, not_needed)
- Invoke src/subtle/ewmh.c (first_time, not_needed)
- Invoke build/subtle/grab.o (first_time, not_needed)
- Invoke src/subtle/grab.c (first_time, not_needed)
- Invoke build/subtle/gravity.o (first_time, not_needed)
- Invoke src/subtle/gravity.c (first_time, not_needed)
- Invoke build/subtle/hook.o (first_time, not_needed)
- Invoke src/subtle/hook.c (first_time, not_needed)
- Invoke build/subtle/panel.o (first_time, not_needed)
- Invoke src/subtle/panel.c (first_time, not_needed)
- Invoke build/subtle/ruby.o (first_time)
- Invoke src/subtle/ruby.c (first_time, not_needed)
- Execute build/subtle/ruby.o

```
gcc -o build/subtle/ruby.o -c -Wall -Werror -Wpointer-arith -Wstrict-prototypes -Wunused -Wshadow -std=gnu99 -g -DDEBUG
-l/usr/X11R6/include -l/usr/X11R6/include -DSUBTLE -l. -lbuild -lsrc -lsrc/shared -lsrc/subtle
-idirafter/usr/local/include/ruby-1.9.1 -idirafter/usr/local/include/ruby-1.9.1/i386-openssl -l/usr/X11R6/include
-l/usr/X11R6/include -l/usr/X11R6/include/freetype2 src/subtle/ruby.c
cc1: warnings being treated as errors
src/subtle/ruby.c: In function 'subRubyLoadSublets':
src/subtle/ruby.c:3847: warning: passing argument 3 of 'scandir' from incompatible pointer type
rake aborted!
Compiler failed with status 1
/home/suborbital/subtle/Rakefile:203:in `block in compile'
/home/suborbital/subtle/Rakefile:138:in `call'
/home/suborbital/subtle/Rakefile:138:in `silent_sh'
/home/suborbital/subtle/Rakefile:201:in `compile'
/home/suborbital/subtle/Rakefile:742:in `block (2 levels) in <top (required)>'
/usr/local/lib/ruby/1.9.1/rake/task.rb:205:in `call'
/usr/local/lib/ruby/1.9.1/rake/task.rb:205:in `block in execute'
/usr/local/lib/ruby/1.9.1/rake/task.rb:200:in `each'
/usr/local/lib/ruby/1.9.1/rake/task.rb:200:in `execute'
/usr/local/lib/ruby/1.9.1/rake/task.rb:158:in `block in invoke_with_call_chain'
/usr/local/lib/ruby/1.9.1/monitor.rb:211:in `mon_synchronize'
/usr/local/lib/ruby/1.9.1/rake/task.rb:151:in `invoke_with_call_chain'
/usr/local/lib/ruby/1.9.1/rake/task.rb:176:in `block in invoke_prerequisites'
/usr/local/lib/ruby/1.9.1/rake/task.rb:174:in `each'
/usr/local/lib/ruby/1.9.1/rake/task.rb:174:in `invoke_prerequisites'
/usr/local/lib/ruby/1.9.1/rake/task.rb:157:in `block in invoke_with_call_chain'
/usr/local/lib/ruby/1.9.1/monitor.rb:211:in `mon_synchronize'
/usr/local/lib/ruby/1.9.1/rake/task.rb:151:in `invoke_with_call_chain'
/usr/local/lib/ruby/1.9.1/rake/task.rb:176:in `block in invoke_prerequisites'
```

```
/usr/local/lib/ruby/1.9.1/rake/task.rb:174:in `each'
/usr/local/lib/ruby/1.9.1/rake/task.rb:174:in `invoke_prerequisites'
/usr/local/lib/ruby/1.9.1/rake/task.rb:157:in `block in invoke_with_call_chain'
/usr/local/lib/ruby/1.9.1/monitor.rb:211:in `mon_synchronize'
/usr/local/lib/ruby/1.9.1/rake/task.rb:151:in `invoke_with_call_chain'
/usr/local/lib/ruby/1.9.1/rake/task.rb:176:in `block in invoke_prerequisites'
/usr/local/lib/ruby/1.9.1/rake/task.rb:174:in `each'
/usr/local/lib/ruby/1.9.1/rake/task.rb:174:in `invoke_prerequisites'
/usr/local/lib/ruby/1.9.1/rake/task.rb:157:in `block in invoke_with_call_chain'
/usr/local/lib/ruby/1.9.1/monitor.rb:211:in `mon_synchronize'
/usr/local/lib/ruby/1.9.1/rake/task.rb:151:in `invoke_with_call_chain'
/usr/local/lib/ruby/1.9.1/rake/task.rb:144:in `invoke'
/usr/local/lib/ruby/1.9.1/rake/application.rb:116:in `invoke_task'
/usr/local/lib/ruby/1.9.1/rake/application.rb:94:in `block (2 levels) in top_level'
/usr/local/lib/ruby/1.9.1/rake/application.rb:94:in `each'
/usr/local/lib/ruby/1.9.1/rake/application.rb:94:in `block in top_level'
/usr/local/lib/ruby/1.9.1/rake/application.rb:133:in `standard_exception_handling'
/usr/local/lib/ruby/1.9.1/rake/application.rb:88:in `top_level'
/usr/local/lib/ruby/1.9.1/rake/application.rb:66:in `block in run'
/usr/local/lib/ruby/1.9.1/rake/application.rb:133:in `standard_exception_handling'
/usr/local/lib/ruby/1.9.1/rake/application.rb:63:in `run'
/usr/local/bin/rake:32:in `'
Tasks: TOP => default => build => subtle => build/subtle/ruby.o
```

@

History

#1 - 03/21/2012 02:03 PM - Christoph Kappel

- Category set to Bugfix
- Status changed from Unconfirmed to Feedback
- Assignee set to Non member users
- Target version set to Xi

What is the version of the installed gcc on your OpenBSD machine?

Edit: I cannot install OpenBSD in virtualbox, because I don't have a CPU with VT-x, so there is currently no way for me to even test that..

#2 - 03/21/2012 11:15 PM - Timmy Steve

Christoph Kappel wrote:

What is the version of the installed gcc on your OpenBSD machine?

Edit: I cannot install OpenBSD in virtualbox, because I don't have a CPU with VT-x, so there is currently no way for me to even test that..

Here is what is on the machine and what is available:

```
$ gcc -v
Reading specs from /usr/lib/gcc-lib/i386-unknown-openbsd5.1/4.2.1/specs
Target: i386-unknown-openbsd5.1
Configured with: OpenBSD/i386 system compiler
Thread model: posix
gcc version 4.2.1 20070719
```

#Available

\$ pkg_info gcc

Information for <ftp://ftp.jaist.ac.jp/pub/OpenBSD/snapshots/packages/i386/gcc-3.3.6p1v0.tgz>

Comment:

GNU compiler collection: core C compiler

Description:

The GNU Compiler Collection (GCC) includes front ends for C, C++, Objective-C, Fortran, Java, and Ada, as well as libraries for these languages (libstdc++, libgcj,...).

GCC development is a part of the GNU Project and uses an open

development environment. Its supports many other platforms in order to foster a world-class optimizing compiler, to attract a larger team of developers, to ensure that GCC and the GNU system work on multiple architectures and diverse environments, and to more thoroughly test and extend the features of GCC.

This package contains the core C compiler.

Maintainer: Marc Espie <espie@openbsd.org>

WWW: <http://gcc.gnu.org/>

Information for <ftp://ftp.jaist.ac.jp/pub/OpenBSD/snapshots/packages/i386/gcc-4.2.4p7v0.tgz>

Comment:

GNU compiler collection: core C compiler

Description:

The GNU Compiler Collection (GCC) includes front ends for C, C++, Objective-C, Fortran, Java, and Ada, as well as libraries for these languages (libstdc++, libgcj,...).

GCC development is a part of the GNU Project and uses an open development environment. Its supports many other platforms in order to foster a world-class optimizing compiler, to attract a larger team of developers, to ensure that GCC and the GNU system work on multiple architectures and diverse environments, and to more thoroughly test and extend the features of GCC.

This package contains the core C compiler.

Maintainer: Marc Espie <espie@openbsd.org>

WWW: <http://gcc.gnu.org/>

Information for <ftp://ftp.jaist.ac.jp/pub/OpenBSD/snapshots/packages/i386/gcc-4.6.2p1.tgz>

Comment:

GNU compiler collection: core C compiler

Description:

The GNU Compiler Collection (GCC) includes front ends for C, C++, Objective-C, Fortran, Java, and Ada, as well as libraries for these languages (libstdc++, libgcj,...).

GCC development is a part of the GNU Project and uses an open development environment. Its supports many other platforms in order to foster a world-class optimizing compiler, to attract a larger team of developers, to ensure that GCC and the GNU system work on multiple architectures and diverse environments, and to more thoroughly test and extend the features of GCC.

This package contains the core C compiler.

Maintainer: The OpenBSD ports mailing-list <ports@openbsd.org>

WWW: <http://gcc.gnu.org/>

What version should I install?

#3 - 03/22/2012 04:19 PM - Christoph Kappel

- Status changed from Feedback to Fixed

- % Done changed from 0 to 100

Applied in changeset [60af832fd27d](#).